

| | | | | |
|---|--------------------------------------|--------------------------------------|--------------------------------------|--------------------------------------|
| Code | 02181310 | 02189310 | 02188310 | 02186310 |
| EAN | 8422248370783 | 8422248370776 | 8422248370769 | 8422248370752 |
| Model | CORONA X NO DRIP 120 | CORONA X NO DRIP 90 | CORONA X NO DRIP 80 | CORONA X NO DRIP 60 |
| Type | Integrated | Integrated | Integrated | Integrated |
| Product fiche according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564 | | | | |
| AEC (Annual Energy consumption) (kWh/annum) | 57,1 | 54,9 | 54,9 | 54,9 |
| EEL class (Energy Efficiency Class) | A | A | A | A |
| FDE (Fluid Dynamic Efficiency) | 29,2 | 29,2 | 29,2 | 29,2 |
| FDE class (Fluid Dynamic Efficiency Class) | A | A | A | A |
| LE (Lighting Efficiency) (lux/W) | 16,1 | 22,3 | 22,3 | 22,3 |
| LE class (Lighting Efficiency Class) | C | B | B | B |
| GFE (Grease Filtering Efficiency) | 69,5 | 69,5 | 69,5 | 69,5 |
| GFE Class (Grease Filtering Efficiency class) | D | D | D | D |
| Air flow at minimum speed (m3/h) | 272,4 | 272,4 | 272,4 | 272,4 |
| Air flow at maximum speed (m3/h) | 608,9 | 608,9 | 608,9 | 608,9 |
| Air flow at intensive speed (TURBO) (m3/h) | 766 | 766 | 766 | 766 |
| Sound Power Level at minimum speed (dB) | 54 | 54 | 54 | 54 |
| Sound Power Level at maximum speed (dB) | 69 | 69 | 69 | 69 |
| Sound Power Level at intensive speed (TURBO) (dB) | 71 | 71 | 71 | 71 |
| Po (Power Consumption in off mode) (W) | 0,48 | 0,48 | 0,48 | 0,48 |
| Ps (Power Consumption in standby) (W) | - | - | - | - |
| Integration directive EU 66/2014 | | | | |
| f (Time Increase Factor) | 0,9 | 0,9 | 0,9 | 0,9 |
| EEL (Energy Efficiency Index) | 53,4 | 52,2 | 52,2 | 52,2 |
| QBEP (Flow Rate at Best Efficiency Point) (m3/h) | 437,8 | 437,8 | 437,8 | 437,8 |
| PBEP (Static Pressure Difference at Best Efficiency Point) (Pa) | 385 | 385 | 385 | 385 |
| WBEP (Electric Power Input at Best Efficiency Point) (W) | 160,5 | 160,5 | 160,5 | 160,5 |
| WL (Nominal Power Consumption of Lighting system) (W) | 6 | 3 | 3 | 3 |
| EMIDDLE (Average Illumination of Lighting system on Cooking surface) (lux) | 96,6 | 67 | 67 | 67 |
| External Dimensions | | | | |
| Width (mm) | 1195 | 895 | 795 | 595 |
| Depth (mm) | 310-350 | 310-350 | 310-350 | 310-350 |
| Total max height(mm) | 334 | 334 | 334 | 334 |
| Total min height(mm) | 334 | 334 | 334 | 334 |
| Outlet Diameter (mm) | 150 | 150 | 150 | 150 |
| Characteristics | | | | |
| Motor type | | | | |
| Motor | BT5 AC 800 | BT5 AC 800 | BT5 AC 800 | BT5 AC 800 |
| Extraction Levels | 3+1 | 3+1 | 3+1 | 3+1 |
| Maximum Power Consumption | 280 | 280 | 280 | 280 |
| Maximum Pressure | 450 | 450 | 450 | 450 |
| Intensive Speed (TURBO) Pressure | 470 | 470 | 470 | 470 |
| Control Type | SDX6I | SDX6I | SDX6I | SDX6I |
| Connectivity | AUTO 2 | AUTO 2 | AUTO 2 | AUTO 2 |
| Automatic removal | - | - | - | - |
| Automatic shut-down timer | √ | √ | √ | √ |
| Electronic Filter Saturation Indicator | √ | √ | √ | √ |
| Filter Type/ layers | Decorative stainless steel, 5 layers | Decorative stainless steel, 5 layers | Decorative stainless steel, 5 layers | Decorative stainless steel, 5 layers |
| Anti-grease Filter Number | 4 | 3 | 2 | 2 |
| Inner Shield | - | - | - | - |
| Glass damped open/closure | √ | √ | √ | √ |
| Air purification function | √ | √ | √ | √ |
| Air quality sensor | - | - | - | - |
| Anti-drip system | Removable tank | Removable tank | Removable tank | Removable tank |
| Lighting | | | | |
| Light Type | SS Led | SS Led | SS Led | SS Led |
| Adjustable Intensity Lighting | √ | √ | √ | √ |
| Gradual switching on and off of the light | - | - | - | - |
| Colour temperature | White 4000°K | White 4000°K | White 4000°K | White 4000°K |
| Nº of Lamps | 2 | 1 | 1 | 1 |
| Installation | | | | |
| Minimum height distance to a electric worktop hob (mm) | 450 | 450 | 450 | 450 |
| Minimum height distance to a gas worktop hob (mm) | 650 | 650 | 650 | 650 |
| Installation with Outlet tube to the exterior / Recirculating | BOTH | BOTH | BOTH | BOTH |
| Easy Installation System | √ | √ | √ | √ |
| Electric Connection | | | | |
| Total Rush Power (W) | 286 | 283 | 283 | 283 |
| Rated Voltage (V) | 220-240 | 220-240 | 220-240 | 220-240 |

| | | | | |
|--|------------------------|------------------------|------------------------|------------------------|
| Network Frequency (Hz) | (220) -50~60/ (240)-50 | (220) -50~60/ (240)-50 | (220) -50~60/ (240)-50 | (220) -50~60/ (240)-50 |
| Electrical Insulation Class | CLASS II | CLASS II | CLASS II | CLASS II |
| Plug | - | - | - | - |
| Connection cable length cm | 110 | 110 | 110 | 110 |
| Accessories / ○ NOT INCLUDED ● INCLUDED | | | | |
| Upper Decorative tube Extension | 02861306 / ○ | 02861306 / ○ | 02861306 / ○ | 02861306 / ○ |
| White Decorative Tube | - | - | - | - |
| Black Decorative Tube | 02861307 / ○ | 02861307 / ○ | 02861307 / ○ | 02861307 / ○ |
| Island Tube Enhancer | - | - | - | - |
| Check Valve | 02832004 / ○ | 02832004 / ○ | 02832004 / ○ | 02832004 / ○ |
| MAX PRO Metal Filter | - | - | - | - |
| Metal Filter | 02800217/ ● | 02800217/ ● | 02800217/ ● | 02800217/ ● |
| DUAL Filter (metal + active charcoal) | - | - | - | - |
| Active Charcoal Filter | 02859398 / ○ | 02859398 / ○ | 02859398 / ○ | 02859398 / ○ |
| Noiseless Flexible Duct | 02893002 / ○ | 02893002 / ○ | 02893002 / ○ | 02893002 / ○ |
| Top outlet motor cover | - | - | - | - |
| FCA kit without duct cover | 02800013 / ○ | 02800013 / ○ | 02800013 / ○ | 02800013 / ○ |
| Decorative panel accessory (APD) (Optional) | - | - | - | - |